(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 9 December 2004 (09.12.2004)

PCT

(10) International Publication Number WO 2004/107479 A1

(51) International Patent Classification7:

H01M 2/14

(21) International Application Number:

PCT/KR2004/001257

(22) International Filing Date: 28 May 2004 (28.05.2004)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data: 10-2003-0034685

30 May 2003 (30.05.2003) KI

(71) Applicant (for all designated States except US): LG CHEM, LTD. [KR/KR]; LG Twin Tower 20, Yoido-dong,, Youngdungpo-gu, Seoul 150-721 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIM, Jee-Ho [KR/KR]; 101-201, Chowon Apartment, Mannyun-dong, Seo-gu, Daejeon 302-740 (KR). YU, Ji-Sang [KR/KR]; 373-1, Guseong-dong, Yuseong-gu, Daejeon 305-338 (KR). CHOI, Jeong-Hee [KR/KR]; 1170-2, Deayeon4-dong, Nam-gu, Busan 608-020 (KR).


- (74) Agent: KIM, Seong-Ki; 14F., Kukdong Building 60-1, Chungmuro3-ka, Chung-ku, Seoul 100-705 (KR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

[Continued on next page]

(54) Title: RECHARGEABLE LITHIUM BATTERY USING SEPARATOR PARTIALLY COATED WITH GEL POLYMER



r: 0.2mm, d: 0.5mm

Disclosed are a (57) Abstract: separator for a battery, which is coated with a gel polymer over 40-60% of total separator area, and a rechargeable lithium battery using the separator. The separator partially coated with a gel polymer reduces the battery resistance so that the battery power can be improved. Additionally, the separator increases electrolyte impregnation rate and provides electrolyte impregnation, uniform thereby improving the life, capacity and high-rate discharge property of a battery. Further, the separator permits electrode reactions to be performed uniformly, thereby preventing lithium precipitation and improving battery safety.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.